



## Options

## SCU 3000 / SCM 4000 / SCS 4010

GmbH

**LISTEC**  
 Linear Sensor Technik

**Options: SCU 3000**

**REL 3000/B**

Motherboard for the insertion of two relay cards (REL 3000/8 or REL 3000/16) into a control unit

**REL 3000/8**

Relay card with 8 floating change-over contacts, prerequisite:  
REL 3000/B

**REL 3000/16**

Relay card with 16 floating change-over contacts, prerequisite:  
REL 3000/B

**REL 3000/UT**

Relay card with floating pre-alarm and under-temperature change-over contacts.

**OPC 3000**

Opto-coupler for the serial interface, built into the unit.

**PRC 3000**

CENTRONICS printer interface , built into the unit.

**TM 3000**

Built-in modem for remote access, with TAE-N plug.

**Software protocols**

Protocols for the connection to PLC's (e.g. SAT, Siemens) or to fire alarm terminal stations (e.g. Bosch-Telecom, Zettler) are available on request.

**Options: SCM 4000 / SCS 4010**

**REL 3000/B**

Motherboard for the insertion of two relay cards (REL 3000/8 or REL 3000/16) into a control unit

**REL 3000/8**

Relay card with 8 floating change-over contacts, prerequisite:  
REL 3000/B

**REL 3000/16**

Relay card with 16 floating change-over contacts, prerequisite:  
REL 3000/B

**REL 3000/UT**

Relay card with floating pre-alarm and under-temperature change-over contacts.

**PRC 3000**

CENTRONICS printer interface , built into the SCM 4000 to print the message list.

**TM 3000**

Built-in modem for remote access, with TAE-N plug.

**Software protocols**

Protocols for the connection to PLC's (e.g. SAT, Siemens) or to fire alarm terminal stations (e.g. Bosch-Telecom, Zettler) are available on request.

**LD 4000**

Line driver for distances greater than 4000m between SCM 4000 and SCS 4010. Complete set for one SCS 4010.

**Optical fibre converters**  
are available on request.

**19" Options for SCU 3000 / SCM 4000 and SCS 4010**

**CAB 19/9**

19" 9U Wall-mounted cabinet, built-up to house one Sensor Control Unit, includes: glass door, swing frame, standard terminal block;

W x H x D: 600 x 478 x 515 mm

**CAB 19/12**

19" U Wall-mounted cabinet, built-up to house two Sensor Control Units, includes: glass door, swing frame, standard terminal block;

W x H x D: 600 x 612 x 515 m