

318*Y TRAILING PVC FLEXIBLE

Flexible plain annealed copper conductors, PVC insulated/PVC sheathed Circular. 300/500 volts grade BS6500 or generally in accordance with BS6500** (* Denotes number of cores)

HO5VVF*

SIZE SQ.MM	CABLE TYPE	RT OF INSULATION MM	NOMINAL DIAMETER OVER LAID UP CORES MM	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
0.5	3182Y	0.6	4.7	6.3	53
0.75	3182Y	0.6	5.4	7.0	63
1.0	3182Y	0.6	5.8	7.4	73
1.5	3182Y	0.7	6.6	8.4	89
2.5	3182Y	0.7	7.8	9.8	140
4.0	3182Y	0.8	9.0	11.0	200
**0.5	3183Y	0.6	5.2	7.0	61
0.75	3183Y	0.6	5.8	7.6	74
1.0	3183Y	0.6	6.3	8.0	86
1.5	3183Y	0.7	7.1	9.1	115
2.5	3183Y	0.8	8.4	10.8	170
4.0	3183Y	0.8	9.7	12.1	250
**0.5	3184Y	0.6	5.8	7.6	73
0.75	3184Y	0.6	6.3	8.1	78
1.0	3184Y	0.6	6.8	8.6	110
1.5	3184Y	0.7	7.8	9.8	140
2.5	3184Y	0.8	9.2	11.4	210
4.0	3184Y	0.8	10.7	12.9	305
**0.5	3185Y	0.6	6.2	8.0	87
0.75	3185Y	0.6	7.0	8.8	105
1.0	3185Y	0.6	7.6	9.6	135
1.5	3185Y	0.7	8.7	10.7	174
2.5	3185Y	0.8	10.3	12.5	265
4.0	3185Y	0.8	11.9	14.3	376

Operating temperature: Maximum 70°C. Minimum flexing 0°C

Conductor identification: Two Core - Brown and Blue
 Three Core - Brown, Blue and Green/Ylw
 Four Core - Brown, Blue, Black and Grn/Ylw
 Five Core - Brown, Blue, 2 Black and Grn/Ylw

Minimum bending radius: 6 x overall diameter

Conductor type: Class 5 flexible.

