

YY CONTROL FLEXIBLE & LSZH CONTROL FLEXIBLE (Continued)

(YY) Flexible plain annealed copper conductors, PVC insulated/PVC sheathed. 300/500 volts grade. Generally in accordance with VDE0250. or (LSZH) Flexible plain annealed copper conductors, XLPE insulated/LSZH sheathed.300/500 volts grade. LSZH version of YY (PVC/PVC) control flexible

SIZE SQ.MM	NUMBER OF CORES	RT OF INSULATION MM	NOMINAL DIAMETER OVER LAID UP CORES MM	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
0.5	2	0.5	3.9	5.5	40
0.75	2	0.5	4.3	5.9	50
1.0	2	0.5	4.6	6.2	55
1.5	2	0.5	5.2	6.8	80
2.5	2	0.6	6.4	8.4	135
4.0	2	0.8	8.4	10.4	197
6.0	2	0.8	9.8	12.0	225
10	2	1.0	12.4	14.8	460
16	2	1.0	14.6	17.2	610
25	2	1.2	18.8	23.6	860
0.5	3	0.5	4.2	5.8	50
0.75	3	0.5	4.6	6.2	60
1.0	3	0.5	4.9	6.5	70
1.5	3	0.5	5.6	7.2	95
2.5	3	0.6	6.9	8.9	165
4.0	3	0.8	9.0	11.2	250
6.0	3	0.8	10.6	12.8	305
10	3	1.0	13.4	15.8	590
16	3	1.0	15.8	18.4	800
25	3	1.2	20.4	28.4	1400
35	3	1.2	23.2	31.9	1840
50	3	1.4	28.2	37.7	2550
0.5	4	0.5	4.8	6.2	65
0.75	4	0.5	5.1	6.7	70
1.0	4	0.5	5.5	7.1	85
1.5	4	0.5	6.3	8.1	120
2.5	4	0.6	7.7	9.7	200
4.0	4	0.8	10.1	12.9	300
6.0	4	0.8	11.9	14.3	390
10	4	1.0	15.0	17.6	720
16	4	1.0	17.7	20.5	1000
25	4	1.2	22.8	31.5	1800
35	4	1.2	26.0	35.3	2380
50	4	1.4	31.6	41.7	3290
70	4	1.4	35.2	46.2	4370
95	4	1.6	40.2	52.7	5860
120	4	1.6	45.9	58.6	7150
0.5	5	0.5	5.1	6.7	70
0.75	5	0.5	5.7	7.3	85
1.0	5	0.5	6.1	7.7	100
1.5	5	0.5	7.0	9.0	150
2.5	5	0.6	8.6	10.8	255
4.0	5	0.8	11.3	13.7	355
6.0	5	0.8	13.2	15.6	470
10	5	1.0	16.7	19.5	865
16	5	1.0	19.7	22.7	1250
25	5	1.2	25.4	34.7	2220
35	5	1.2	29.0	38.9	2790
0.5	7	0.5	5.7	7.3	80
0.75	7	0.5	6.3	7.9	105
1.0	7	0.5	6.7	8.3	125
1.5	7	0.5	7.8	9.8	185
2.5	7	0.6	9.6	11.8	305
4.0	7	0.8	12.6	15.2	440
6.0	7	0.8	14.7	17.3	625
0.5	10	0.5	7.8	9.4	120
0.75	10	0.5	8.6	10.2	150
1.0	10	0.5	9.2	10.8	180
1.5	10	0.5	10.4	12.6	270
2.5	10	0.6	12.8	15.2	357



Date created: 02.04.2003

Telephone: +44 (0)121 508 6890

Fax: +44 (0)121 508 6891

Web: www.cablesbritain.com

Email: sales@cablesbritain.com