

**MULTIPAIR**
**OVERALL SCREENED**

24 AWG * UL 2464 * VOLTAGE:300v * MAX TEMP: 80 DEG C
--

**DESCRIPTION:**

STRANDED TINNED COPPER CONDUCTORS,PVC INSULATED,OVERALL ALUMINIUM POLYESTER SCREEN, T.C.DRAINWIRE,PVC SHEATH GREY.

**APPLICATION:**

FOR VOICE OR DATA TRANSMISSION AND EIA RS-232

REFERENCE	PAIRS	SQ.MM	STRANDED (MM)	AWG	NOM OD	KG/KM
9501		0.22	7/0.20	24	4.00	19.3
9502		0.22	7/0.20	24	5.6	31.4
9503		0.22	7/0.20	24	6.00	39.9
9504		0.22	7/0.20	24	6.7	48.9
9505		0.22	7/0.20	24	7.4	56.9
9506		0.22	7/0.20	24	7.5	69.0
9507		0.22	7/0.20	24	7.6	72.2
9508		0.22	7/0.20	24	8.3	78.8
9509		0.22	7/0.20	24	8.6	92.8
9510		0.22	7/0.20	24	9.7	98.0
9515		0.22	7/0.20	24	10.9	135.6
9519		0.22	7/0.20	24	11.7	164.6
9525		0.22	7/0.20	24	13.2	215.0
9550		0.22	7/0.20	24	17.8	398.5

**MAXIMUM CONDUCTOR RESISTANCE AT 20 DEG C (OHM/KM) 76**

NOMINAL CAPACITANCE BETWEEN CONDUCTORS AT 1 KHz (Pf / M)

1 Pair 131, Balance 98

NOMINAL CAPACITANCE CONDUCTOR TO SCREEN AT 1 KHz (Pf / M)

1 Pair 243, Balance 164

Date created: 02.04.2003

Telephone: +44 (0)121 508 6890

Fax: +44 (0)121 508 6891

Web: [www.cablesbritain.com](http://www.cablesbritain.com)

Email: [sales@cablesbritain.com](mailto:sales@cablesbritain.com)