

**MULTIPAIR**

**INDIVIDUALLY SCREENED**

24 AWG \* UL 2493 \* VOLTAGE:300v \* MAX TEMP: 60 DEG C

DESCRIPTION:

STRANDED TINNED COPPER CONDUCTORS, CELLULAR POLYPROPYLENE INSULATED, INDIVIDUALLY ALUMINIUM POLYESTER SCREEN, T.C.DRAINWIRE, PVC SHEATH GREY.

APPLICATION:

EIA RS-422 COMPUTER CABLES.

REFERENCE	PAIRS	SQ.MM	STRANDED (MM)	AWG	NOM OD	KG/KM
9729	2	0.22	7/0.2	24	8.5	65
9730	3	0.22	7/0.2	24	8.9	81
9731	6	0.22	7.02	24	12.0	130
9732	9	0.22	7/0.2	24	14.5	210
9734	12	0.22	7/0.2	24	16.0	245
9735	15	0.22	7/0.2	24	17.8	285
9737	19	0.22	7/0.2	24	19.0	325
9738	27	0.22	7/0.2	24	22.2	510

CAPACITANCE BETWEEN CONDUCTORS (Pf / M) 41

CAPACITANCE BETWEEN 1 CONDUCTOR AND OTHER CONDUCTORS CONNECTED TO SHIELD (Pf / M) 76.

