

**MULTIPAIR**

**INDIVIDUALLY SCREENED**

22 AWG \* UL 2919 \* VOLTAGE:30v \* MAX TEMP: 80 DEG C

**DESCRIPTION:**

STRANDED TINNED COPPER CONDUCTORS, POLYPROPYLENE INSULATED, EACH PAIR INDIVIDUALLY ALUMINIUM POLYESTER SCREENED T.C.DRAIN WIRE, PVC SHEATH GREY.

**APPLICATION:**

COMPUTER CABLES.

REFERENCE	PAIRS	SQ.MM	STRANDED (MM)	AWG	NOM OD	KG/KM
8777	3	0.35	7/0.254	22	7.7	79
8778	6	0.35	7/0.254	22	10.2	138
8774	9	0.35	7/0.254	22	11.3	182
8775	11	0.35	7/0.254	22	11.65	210
9768	12	0.35	7/0.254	22	11.65	215
8776	15	0.35	7/0.254	22	14.7	310
9769	17	0.35	7/0.254	22	14.9	330
8769	19	0.35	7/0.254	22	16.00	360
8773	27	0.35	7/0.254	22	19.00	500
9767	37	0.35	7/0.254	22	21.3	525

**NOMINAL CAPACITANCE BETWEEN CONDUCTORS AT 1 KHz  
(Pf / M) 98**

NOMINAL CAPACITANCE CONDUCTOR TO SCREEN AT 1 KHz (Pf / M) 180