

TWINAXIAL

OVERALL SCREENED

20 AWG * UL 2092 * VOLTAGE:300v * MAX TEMP: 60 DEG C

DESCRIPTION:

STRANDED TINNED COPPER CONDUCTORS, POLYETHYLENE INSULATED, OVERALL ALUMINIUM POLYESTER SCREEN, T.C.DRAINWIRE, TINNED COPPER BRAID SCREEN,PVC SHEATH BLUE

APPLICATION:

POINT OF SALE CABLE:BROADCAST AND COMPUTER CABLE.

REFERENCE	PAIRS	SQ.MM	STRANDED (MM)	AWG	NOM OD	KG/KM
9272	1	0.56	7/0.32	20	6.2	59

NOMINAL CAPACITANCE BETWEEN CONDUCTORS AT 1 KHz (Pf / M) 65.

NOMINAL CAPACITANCE CONDUCTOR TO SCREEN AT 1 KHz (Pf / M) 110.

20 AWG * UL 2498 * VOLTAGE 300v * MAX TEMP: 80 DEG C.

1 X TINNED COPPER, 1 BARE COPPER CONDUCTOR,POLYETHYLENE INSULATED,POLYETHYLENE BEDDING,COPPER WIRE BRAID,PVC SHEATH BLACK.

APPLICATION:

POINT OF SALE CABLE: BROADCAST AND COMPUTER CABLE.

REFERENC E	PAIRS	SQ.MM	STRANDED (MM)	AWG	NOM.OD	KG/KM
9207	1	0.56	7/0.32	20	8.4	97

NOMINAL CAPACITANCE BETWEEN CONDUCTORS AT 1KHz (Pf / m) 51.

NOMINAL CAPACITANCE CONDUCTOR TO SCREEN AT 1 KHz (Pf / m) 90.