

## 7-1-\*C SCREENED MULTICORE Def. Stan. Sub Miniature

Flexible tinned annealed copper conductors, PVC insulated/Polyester taped/Tinned Copper braid screen/  
PVC sheathed, Circular. 250 volts grade R.M.S (at 1600 c/s) to Def Stan 61-12 Part 4 or \*\* Generally to  
Def Stan 61-12 Part 4. (\* Denotes number of cores)

NUMBER OF CORES	NATO NO. 6145-99-110-	CABLE REF	DIAMETER OVER LAID UP CORES MM	DIAMETER OF BRAID WIRE MM	DIAMETER OVER COLLECTIVE SCREEN MM	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
2	8583	7-1-2C	1.4	0.10	1.9	2.7	13
3	8586	7-1-3C	1.5	0.10	2.0	2.9	15
4	8589	7-1-4C	1.7	0.10	2.2	3.1	17
6	8592	7-1-6C	2.1	0.10	2.6	3.5	21
12	8595	7-1-12C	2.9	0.10	3.4	4.3	31
**15	-	7-1-15C	3.2	0.15	3.9	4.8	41
18	8598	7-1-18C	3.5	0.15	4.3	5.4	50
25	8601	7-1-25C	4.2	0.15	5.0	6.1	62
36	8604	7-1-36C	4.9	0.15	5.7	6.8	79
50	8607	7-1-50C	5.9	0.15	6.7	8.0	100
60	8610	7-1-60C	6.3	0.15	7.1	8.4	120

