

190°C PTFE equipment wire to DEF STAN 61-12 Part 8 and BS.G210

Single core, Silver plated copper conductor, PTFE insulated

Wire Size No	Size SQ.MM	Stranding MM	Conductor Diameter MM	Insulation Thickness Minimum	Insulation Thickness Nominal MM	Overall Diameter Minimum MM	Overall Diameter Nominal MM	Weight KG/KM	Maximum-Resistance OHMS/KM at 20°C D	Amperage at 150°C A	Voltage AC/RMS V	Type
28	0.09	7/.12	0.38	0.10	0.15	0.56	0.71	1.32	244.00	3.0	250	A
24	0.22	7/.20	0.60	0.10	0.15	0.80	0.95	2.85	88.30	6.0	250	A
22	0.33	19/.15	0.75	0.10	0.15	0.95	1.10	4.22	58.60	8.0	250	A
24	0.22	7/.20	0.60	0.20	0.25	1.00	1.20	3.52	88.30	6.0	500	B
22	0.33	19/.15	0.75	0.20	0.25	1.15	1.35	5.06	58.60	8.0	500	B
20	0.59	19/.20	1.00	0.20	0.25	1.40	1.60	7.44	32.50	11.0	500	B
18	0.93	19/.25	1.25	0.20	0.25	1.65	1.85	8.85	20.60	15.0	500	B
20	0.59	19/.20	1.00	0.33	0.40	1.66	1.92	9.18	32.50	11.0	1000	C
16	1.34	19/.30	1.50	0.33	0.40	2.16	2.46	19.25	14.30	20.0	1000	C
12	3.02	19/.45	2.25	0.33	0.40	2.91	3.31	36.0	6.28	35.0	1000	C
10	4.65	37/.40	2.80	0.33	0.40	3.46	3.86	54.0	4.01	47.0	1000	C

Minimum Bending Temperature: -75°C,



Date created: 02.04.2003

Telephone: +44 (0)121 508 6890

Fax: +44 (0)121 508 6891

Web: www.cablesbritain.com

Email: sales@cablesbritain.com