

## NYY PVC INSULATED POWER CABLES (Continued)

Plain annealed copper conductors, PVC insulated/PVC sheathed. 1000 volts grade to VDE 0271 and IEC 502 (where applicable).

### NYY Power Cables

SIZE SQ.MM	CONDUCTOR TYPE	NUMBER OF CORES	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
1.5	re	4	13.0	250
2.5	re	4	14.0	310
4	re	4	15.5	420
6	re	4	17.0	530
10	re	4	19.0	730
16	re	4	21.5	1030
25	rm	4	25.5	1550
35	rm	4	28.5	2050
50	rm	4	33.0	2740
70	sm	4	34.5	3220
95	sm	4	39.0	4390
120	sm	4	42.5	5380
150	sm	4	48.0	6580
185	sm	4	52.5	8220
240	sm	4	60.0	10570
300	sm	4	68.0	13250

SIZE SQ.MM	CONDUCTOR TYPE	NUMBER OF CORES	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
1.5	re	5	13.5	290
2.5	re	5	15.0	360
4	re	5	17.0	500
6	re	5	19.5	640
10	re	5	20.5	880
16	re	5	23.0	1220

SIZE SQ.MM	CONDUCTOR TYPE	NUMBER OF CORES	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
1.5	re	7	14.5	340
2.5	re	7		
4	re	7		
6	re	7		
10	re	7		
16	re	7		

