

High Temperature

TRI-RATED FLEXIBLE 105°C

Single core, flexible plain annealed copper conductor, Heat resistant PVC insulation. Panel Wire to BS6231 Type CK and UL/CSA approved. 600/1000 volts grade

SIZE SQ.MM	CLASS OF CONDUCTOR	RT OF INSULATION MM	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
0.5	5	0.8	2.6	12
0.75	5	0.8	2.8	15
1.0	5	0.8	3.0	18
1.5	5	0.8	3.3	23
2.5	5	0.8	3.8	34
4	5	0.8	4.3	50
6	5	0.8	4.9	71
10	5	1.0	6.3	123
16	5	1.0	9.0	207
25	5	1.2	10.4	303
35	5	1.2	11.9	412
50	5	1.4	14.7	607
70	5	1.4	16.8	837
95	5	1.6	18.8	1080
120	5	1.6	20.4	1280
150	5	1.8	23.0	1630
185	5	2.0	26.0	1940
240	5	2.0	29.5	2550
*300	5	2.4	32.7	3140

Operating Temperature: Maximum 105°C, Minimum flexing 0°C

*UL/BS Dual rated only



Date created: 02.04.2003

Telephone: +44 (0)121 508 6890

Fax: +44 (0)121 508 6891

Web: www.cablesbritain.com

Email: sales@cablesbritain.com