

Multipair Instrumentation Cables - BS5308

BS 5308 Part 2/Type 2 (PVC insulated) - ARMOURED

SPECIFICATION

Plain annealed copper conductors, PVC insulated, collective Aluminium-Mylar screened, including drain wire, PVC bedded, steel wire armoured, PVC sheathed.

Pairs : Two insulated conductors uniformly twisted together forming a pair. Lay length should not exceed 100mm and layed in a manner that the two wires forming the pair cannot be dissociated by normal handling. Two pair cables layed up in a quad formation.

Screens : Collectively screened by a laminated, bonded aluminium/polyester tape. The metallic side of the screens are in contact with one or more tinned annealed copper drain wire, running throughout the cable length. The cross sectional area of the drain wire is not less than 0.5mm sq.

Colour Of Sheath : Blue and Black.

Operating Temperature : 0 C - 70 C.

Minimum Bending Radius : 6 x Overall Diameter.
300/500 Volt grade.

Pair	Overall Diameter mm	Weight kg/km	Gland Size
0.5mm sq. (16/0.20)			
1	10.8	50	20ss
2	11.7	130	20ss
5	17.3	220	32
10	22.3	370	32
20	28.5	660	40
30	33.3	960	50
50	41.5	1590	50s
0.75mm sq. (24/0.20)			
1	11.1	60	20ss
2	12.3	155	20
5	19.2	265	25
10	24.7	455	32
20	30.7	790	40
30	36.9	1150	50s
50	46.9	1900	63s
1.5mm sq (7/0.50)			
1	12.3	75	20ss
2	13.7	205	20s
5	21.5	305	25
10	27.8	560	32
20	35.1	870	40
30	41.9	1300	50s
50	55.0	2120	63s

Date created: 02.04.2003

Telephone: +44 (0)121 508 6890

Fax: +44 (0)121 508 6891

Web: www.cablesbritain.com

Email: sales@cablesbritain.com