

Mines & Misc Quarries

TYPE 21 PLIABLE ARMoured TRAILING FLEX - HOFr

Flexible tinned annealed copper conductors, Ethylene Propylene (EP) Rubber insulated, laid up around an elastomeric heat resisting cradle centre/Polychloroprene (PCP) bedded/Pliable Wire Armoured/ Polychloroprene (PCP) sheathed. 640/1100 volts grade to BS6708 (where applicable).

SIZE SQ.MM	CLASS OF CONDUCTOR	NUMBER OF CORES	RT OF INSULATION MM	DIAMETER OVER LAID UP CORES MM	NOMINAL DIAMETER OVER BEDDING MM	ARMOUR SIZE / STRANDING MM	MAXIMUM OVERALL DIAMETER MM	WEIGHT KG/KM
2.5	5	4	1.4	4.8	18.0	7/45	28.6	1150
4	5	4	1.4	5.4	19.4	7/45	30.1	1280
6	5	4	1.5	6.6	24.8	7/71	38.8	2270
10	5	4	1.5	7.6	27.2	7/71	41.0	2630
16	5	4	1.5	8.7	29.9	7/71	44.0	3050
25	5	4	1.6	10.3	33.7	7/71	49.8	3870
35	5	4	1.6	11.7	37.1	7/9	56.1	5000
50	5	4	1.7	13.7	42.0	7/9	61.8	6160
70	5	4	1.8	16.0	50.1	7/9	71.4	8150
95	5	4	2.0	18.5	56.2	7/9	78.6	9880
120	5	4	2.2	20.4	63.2	7/1.25	89.0	13320
150	5	4	2.3	22.6	68.5	7/1.25	95.3	16220



Date created: 02.04.2003

Telephone: +44 (0)121 508 6890

Fax: +44 (0)121 508 6891

Web: www.cablesbritain.com

Email: sales@cablesbritain.com