

Rubber Flexible

RUBBER PLATFORM

Flexible plain annealed copper conductors Thermoplastic (TP) Rubber insulated, Thermoplastic (TP) Rubber sheathed, 600/1000 volts grade

SIZE SQ.MM	CLASS OF CONDUCTOR	NUMBER OF CORES	RT OF INSULATION MM	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
1.5	5	4	0.7	16.0 x 5.0	110
2.5	5	4	0.8	19.0 x 5.7	170
4	5	4	0.8	21.0 x 6.5	250
6	5	4	0.8	23.5 x 7.0	330
10	5	4	1.0	29.0 x 9.0	550
16	5	4	1.0	35.0 x 10.4	800
25	5	4	1.2	45.5 x 13.5	1350
35	5	4	1.2	50.5 x 14.8	1800
50	5	4	1.2	56.0 x 16.5	2400
1.5	5	8	0.7	29.0 x 5.0	220
2.5	5	8	0.8	35.0 x 5.7	330
1.5	5	12	0.8	41.0 x 5.0	320
2.5	5	12	0.8	51.0 x 5.7	490

Maximum conductor temperature:85°C, Minimum flexing -30°C

Core Identification:

4 Core - Black, Light Blue, Green/Yellow & Brown
5 Core plus, Printed numbers with One Green/Yellow Core

This cable is also manufactured in a PVC configuration

