

Rubber Flexible

318* TRS TRAILING FLEXIBLE

Flexible tinned annealed copper conductors, EI4 60°C Rubber insulated, Tough Rubber (TR) sheathed. 300/500 volts grade, to BS7919 & BS6007

Harmonised Code: H05RR-F*

(* denotes quantity of cores)

SIZE SQ.MM	NUMBER OF CORES	RT OF INSULATION MM	NOMINAL DIAMETER OVER LAID UP CORES MM	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
**0.5	2	0.6	4.4	7.8	53
0.75	2	0.6	4.8	8.2	63
1.0	2	0.6	5.2	8.8	77
1.5	2	0.8	6.6	10.5	115
2.5	2	0.9	7.8	12.5	165
**0.5	3	0.6	4.8	8.2	62
0.75	3	0.6	5.2	8.8	78
1.0	3	0.6	5.7	9.2	90
1.5	3	0.8	7.2	11.0	135
2.5	3	0.9	8.5	13.0	195
0.75	4	0.6	5.8	9.6	94
1.0	4	0.6	6.3	10.0	110
1.5	4	0.8	8.0	12.5	170
2.5	4	0.9	9.5	14.0	245
0.75	5	0.6	6.5	11.0	110
1.0	5	0.6	7.1	11.5	130
1.5	5	0.8	9.0	13.5	195
2.5	5	0.9	10.6	15.5	290

Operating temperature: Maximum 60°.

** H05RR-F does not apply (National type)

Conductor identification:
 Two Core - Brown & Blue
 Three Core - Brown, Blue & Green/Yellow
 Four Core - Brown, Blue, Black & Green/Yellow
 Five Core - Brown, Blue, 2 Black & Green/Yellow

Conductor: Class 5 flexible

Minimum bending radius: 6 x overall diameter,



Date created: 02.04.2003

Telephone: +44 (0)121 508 6890

Fax: +44 (0)121 508 6891

Web: www.cablesbritain.com

Email: sales@cablesbritain.com