

## 657TQ HOFR TYPE 'B' (Continued)

Tinned annealed copper conductors, EPR (Ethylene Propylene Rubber) insulated/CSP (Chlorosulphonated Polyethylene) sheathed, 600/1000 volts grade to BS6883 Type B (where applicable).

Sheath Colour: Black. HOFR: Heat and Oil resistant, Flame retardant.

### THREE CORE : REF 6573TQ

SIZE SQ.MM	NOMINAL DIAMETER OVER LAID UP CORES MM	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
1.0	6.2	8.4	100
1.5	6.9	9.3	130
2.5	7.9	10.4	180
4	10.1	12.7	270
6	11.4	13.9	350
10	14.2	17.2	565
16	16.4	19.5	795
25	20.8	24.4	1240
35	22.8	26.5	1480
50	26.2	30.3	1960
70	30.1	34.7	2700
95	34.8	39.7	3680
120	38.5	43.8	4490
150	42.8	48.4	5550
185	47.5	53.9	6910
240	54.0	61.1	8980
300	60.2	67.6	11170

### FOUR CORE : REF 6574TQ

SIZE SQ.MM	NOMINAL DIAMETER OVER LAID UP CORES MM	NOMINAL OVERALL DIAMETER MM	WEIGHT KG/KM
1.0	7.0	9.3	145
1.5	7.8	10.1	155
2.5	9.0	11.4	215
4	11.4	13.9	335
6	12.9	15.4	445
10	16.0	18.9	700
16	18.4	21.7	1010
25	23.5	25.8	1570
35	25.7	27.8	1880
50	29.5	32.0	2510
70	33.9	36.2	3490
95	39.2	42.1	4780
120	43.4	45.8	5830
150	48.0	50.5	7210
185	53.4	56.2	8960
240	60.7	65.8	11660
300	67.7	73.5	14530



Date created: 02.04.2003

Telephone: +44 (0)121 508 6890

Fax: +44 (0)121 508 6891

Web: [www.cablesbritain.com](http://www.cablesbritain.com)

Email: [sales@cablesbritain.com](mailto:sales@cablesbritain.com)